

Ideal consumables to be purchased with a Gas Chromatograph

| Product-Number | Quantity | Description | Where used | More Information |
|----------------|----------|---|-----------------------|------------------|
| 5181-1210 | 100 | Crimp Caps (100/PK) | All Autosamplers | 5968-7132E |
| 5181-3375 | 100 | 2 ml Crimp Vial (100/PK) | All Autosamplers | |
| 5182-0717 | 100 | Blue screw caps (100/PK) | All Autosamplers | |
| 5182-0715 | 100 | 2 ml Screw cap vial (100/PK) | All Autosamplers | |
| 5183-4763 | 1 | Electronic Crimper | Crimp Vials | 5968-9618E |
| 18740-20885 | 10 | Gold plated seal | Split/Splitless Inlet | 5967-5629E |
| 19251-60540 | 10 | Standard Split Liner | Split/Splitless Inlet | 5967-5629E |
| 5183-4702 | 1 | Liner for critical split injections (25/pk) | Split/Splitless Inlet | 5967-5629E |
| 5182-3481 | 1 | Hydrogen generator 150cc/min | FID | 5968-5602E |
| 5182-3484 | 1 | Zero air generator 3.5 L/min | FID | 5968-5602E |
| 5181-3360 | 5 | 10ul Syringe for Autosampler (6/PK) | All Autosamplers | 5968-5823E |
| 5182-9765 | 1 | GC Buddy, (Column Cutter, Ferrule Remover, Liner Extractor, and more) | All GCs | |
| 19199N | 1 | GC Install Kit <ul style="list-style-type: none"> • Snoop leak detector fluid 8oz • Nuts and Ferrule Kit • Copper Tubing, 50 ft x 1/8" • 1/8" Tees, brass 4/pk • Tubing Cutter, 1/8" to 5/8" OD Tubing • 1/8" brass caps, 6/pk • Oxygen Trap, 1/8" Glass Indicating • Oxygen Trap, 1/8" High Capacity, 2.5 liter • Moisture Trap, 100 cc, 1/8" Glass Indicating • Activated Charcoal Trap S-type, 1/8" • Split Vent Trap Kit | All GCs | |



Agilent Technologies

Innovating the HP Way

| Product-Number | Quantity | Description | Where used | More Information |
|----------------|----------|--|------------|------------------|
| 19199M | 1 | GC Install Kit <ul style="list-style-type: none"> • Snoop leak detector fluid 8oz • Nuts and Ferrule Kit • Copper Tubing, 50 ft x 1/8" • 1/8" Tees, brass 4/pk • Tubing Cutter, 1/8" to 5/8" OD Tubing • 1/8" brass caps, 6/pk • Nut Driver, 7 mm • Screwdriver, Torx T 10 • Screwdriver, Torx, T 20 • Wrench, column nut, 1/4" x 5/16" • Wrench, open end, 7/16" x 9/16" • Wrench, open end, 7/16" and 3/8" • Wrench, open end, 7/16" and 1/2" | All GCs | |
| 5183-4775 | 1 | Installation Kit for GC with FID <ul style="list-style-type: none"> • FID Gas Purification System - Dedicated three position system for purifying all gases used in an FID-equipped GC. Includes the new Triple Filter Cartridge for carrier gas, and two new Fuel Gas Filter Cartridges for both Hydrogen and Zero Air. • Snoop leak detector fluid 8oz • Nuts and Ferrule Kit • Copper Tubing, 50 ft x 1/8", pre-cleaned • 1/8" Tees, brass 4/pk • Tubing Cutter, 1/8" to 5/8" OD Tubing • 1/8" brass caps, 6/pk • Split Vent Trap Kit | All GCs | |

For sales support regarding consumables contact us via e-mail (ESMC-CS@agilent.com) or Rainer Vömel (phone +49-7243-602-673).



Copyright © 2000
 Agilent Technologies, Inc.
 5980 -1962E